



Hellenic Gas Transmission System Operator S.A.
357-359 Messogion Av., GR 152 31 Halandri
Tel.: 213 088 4000
Fax: 210 674 9504
Email: desfa@desfa.gr

TECHNICAL SPECIFICATION

Doc No: DSF-SPC-PIP-024

Rev. 2

Page 1 of 14

HIGH PRESSURE (HP) TRANSMISSION SYSTEMS

PLUG VALVES DN > 50

JUNE 2022

This document is the property of DESFA S.A. and shall not be reproduced, copied or used for any purpose, other than for which it is specially furnished.

2	Third Issue	02-06-2022	PG	PG	DK
1	Second Issue	30-06-2021	MP	DK	TPI
0	First Issue	05-04-2011	PQ DPT.		V.G.
REV	DESCRIPTION	DATE	PRPD	CHKD	APVD



Page 2 of 14

[illegible]



Hellenic Gas Transmission System Operator S.A.
357-359 Messogion Av., GR 152 31 Halandri
Tel.: 213 088 4000
Fax: 210 674 9504
Email: desfa@desfa.gr

TECHNICAL SPECIFICATION

Doc No: DSF-SPC-PIP-024

Rev. 2

Page 3 of 14

Table of Contents

1	SCOPE	5
1.1	ITEM	5
1.2	SERVICE	5
1.3	APPLICATION	5
1.4	ADDITIONAL INFORMATION	5
2	REFERENCES	5
2.1	REFERENCE DOCUMENTS	5
2.2	REFERENCE CODES AND STANDARDS	6
3	GENERAL REQUIREMENTS	6
3.1	UNITS	6
3.2	PRESSURE RATING	6
3.3	PATTERN	6
3.4	CONSTRUCTION	6
3.5	MATERIALS	8
3.6	NON DESTRUCTIVE EXAMINATION	9
3.7	FIRE TEST	9
3.8	FACTORY TEST	9
3.9	SURFACE TREATMENT	9
3.10	MARKING	10
3.11	TAGGING	10
3.12	DELIVERY	10
4	ADDITIONAL REQUIREMENTS FOR HYDROGEN USE	10
4.1	General Remarks	10
4.2	Materials	11
4.3	Testing	11
5	SUPPLEMENTARY REQUIREMENTS	11
6	TECHNICAL DOCUMENTATION	12
6.1	QUANTITY	12
6.2	INSPECTION AND CERTIFICATION	12



Hellenic Gas Transmission System Operator S.A.
357-359 Messogion Av., GR 152 31 Halandri
Tel.: 213 088 4000
Fax: 210 674 9504
Email: desfa@desfa.gr

TECHNICAL SPECIFICATION

Doc No: DSF-SPC-PIP-024

Rev. 2

Page 4 of 14

6.3	DOCUMENT REQUIREMENTS	12
6.4	VALVE CERTIFICATION PACKAGE	13
7	SHIPMENT	14



Hellenic Gas Transmission System Operator S.A.
357-359 Messogion Av., GR 152 31 Halandri
Tel.: 213 088 4000
Fax: 210 674 9504
Email: desfa@desfa.gr

TECHNICAL SPECIFICATION

Doc No: DSF-SPC-PIP-024

Rev. 2

Page 5 of 14

1 SCOPE

1.1 ITEM

Plug valves DN > 50

1.2 SERVICE

Sweet, natural gas with sporadic passage of water and glycol.

1.3 APPLICATION

Shut-off.

1.4 ADDITIONAL INFORMATION

Additional information may be given in the Data Sheets and Material Requisition and these documents should be read in conjunction with this material Job Specification.

Any conflict between requirements of this Specification and drawings, Data Sheets and Material Requisition supplementary design data, or Standards codes shall be referred to DESFA for clarification, before proceeding with fabrication of concerned part.

Plug valve Manufacturer shall be responsible to design valves and their components in accordance with the requirements of applicable documents.

In no event, however, are thicknesses, dimensions etc. to be less than those shown on valve drawings unless specific written approval to the contrary is received from DESFA.

2 REFERENCES

Items/equipment to be supplied under this Specification shall comply with the requirements of the latest edition of the Codes, Standards, Specifications and Practices as applicable, except if specifically, modified hereafter:

2.1 REFERENCE DOCUMENTS

- Technical Specification DSF-SPC-MEC-009 [Plant Coating of Buried Valves for Pipeline]
- Technical Specification DSF-SPC-QAC-005 [Shop Inspection of Equipment and Materials for NGT Project]



Hellenic Gas Transmission System Operator S.A.
357-359 Messogion Av., GR 152 31 Halandri
Tel.: 213 088 4000
Fax: 210 674 9504
Email: desfa@desfa.gr

TECHNICAL SPECIFICATION

Doc No: DSF-SPC-PIP-024

Rev. 2

Page 6 of 14

2.2 REFERENCE CODES AND STANDARDS

- 2014/68/EU [Pressure Equipment Directive (PED) of the European Parliament and of the Council of 15 May 2014 on the harmonization of the laws of the Member States relating to the making available on the market of pressure equipment Text with EEA relevance]
- EN 14141 [Valves natural gas transportation in pipelines - Performance and tests]
- EN 10204 [Metallic Products – Types of Inspection Documents]
- EN 1092-1 [Flanges and their joints - Circular flanges for pipes, valves, fittings and accessories, PN designated - Part 1: Steel flanges]
- EN 1503-1 [Valves - Materials for bodies, bonnets and covers - Part 1: Steels specified in European standards]
- EN 1594 [Gas supply systems - Pipelines for maximum operating pressure over 16 bar - Functional requirements]
- EN 13942 [Petroleum and natural gas industries - Pipeline transportation systems - Pipeline valves]
- MSS SP-44 [Steel Pipeline Flanges]

3 GENERAL REQUIREMENTS

3.1 UNITS

Metric for all units.

3.2 PRESSURE RATING

Refer to Data Sheet or Material Requisition.

3.3 PATTERN

Refer to Data Sheet for short, regular or venture pattern requirement.

3.4 CONSTRUCTION

3.4.1 PLUG

Tapered.



Hellenic Gas Transmission System Operator S.A.
357-359 Messogion Av., GR 152 31 Halandri
Tel.: 213 088 4000
Fax: 210 674 9504
Email: desfa@desfa.gr

TECHNICAL SPECIFICATION

Doc No: DSF-SPC-PIP-024

Rev. 2

Page 7 of 14

3.4.2 LUBRICATION

Required through lubricant check valve. Lubricant grooves shall disconnect lubricant chamber and pipe bore under plug movement. Any lubricants shall be suitable for the Minimum Winter Design Temperature in the location where they are to be installed.

Valves for use below ground shall have the injection line(s) extended to near valve operator. A check valve shall be mounted where the injection line is fixed to the body. Screwed joints are only acceptable if fully engaged and seal welded.

3.4.3 MECHANICAL ADJUSTMENT OF PLUG

Required by bottom screw.

3.4.4. STEM/PLUG CONNECTION

Design shall prevent lateral strain on stem for valves class PN 50 and higher (equaliser ring).

3.4.5 STEM SEALS

Dual O-rings or alternate design of equivalent or better quality.

Ingress of water between stem and gland shall be prevented (e.g. weather seal).

3.4.6 STEM STOPS

Required

3.4.7 WELDING ENDS

Shall match the diameters of the abutting ends within a tolerance of ± 1.6 mm. Refer to DATA SHEET for abutting pipe dimensions.

Beveling shall be as specified in EN 14141.

3.4.8 FLANGES

Raised Face or Ring Joint as per EN 1092-1 or MSS SP-44. Refer to Data Sheet for type. Bore to be derived from abutting pipe dimensions, see Data Sheet.

3.4.9 VALVE OPERATION

Refer to Data Sheet for method.

3.4.10 LIFTING EYES

Required for valves size DN > 150.



Hellenic Gas Transmission System Operator S.A.
357-359 Messogion Av., GR 152 31 Halandri
Tel.: 213 088 4000
Fax: 210 674 9504
Email: desfa@desfa.gr

TECHNICAL SPECIFICATION

Doc No: DSF-SPC-PIP-024

Rev. 2

Page 8 of 14

3.4.11 STEAM EXTENSION HOUSING

Housing shall be rigidly mounted to valve body by flanges (or similar joint). Housing design and its connections to valve and gear operator shall prevent any ingress of water, humid air or other substances which may affect valve operation, particularly during cold periods. Where air tightness cannot be ensured, filling of the housing with a suitable lubricant can be considered acceptable.

3.4.12 SUPPORT RIBS AND LEGS

Refer to Data Sheet for requirement.

Where a support is required the size of the area actually transferring the load to a base below shall be at least 20 mm² per kilogram of valve weight.

3.5 MATERIALS

3.5.1 GENERAL

Only fully killed fine grain carbon steel conforming to EN 14141 and EN 1503-1 shall be used.

When normalized and tempered materials are specified, the tempering shall be performed prior to any welding unless specifically otherwise authorized in writing by DESFA. The tempering temperature shall be 10°C higher than that required for post weld Heat Treatment, unless otherwise specified. Attention is drawn to section 3 detailing certification requirements.

Body and cover shall have impact tests for each type of material used as per EN 14141 and EN 10045-1. The test temperature shall be -20°C or lower with the following acceptance criterion: Mean value from the 3 tests 31 Joules or better, with the lowest single value 24 Joules. Mating seating surfaces shall have a hardness differential of at least 50 HB.

3.5.2 BODY (INCL. WELDING ENDS)

As per EN 14141 and essential details are as follows:

- Carbon content C shall be $\leq 0.21\%$ on heat analysis.
- Carbon equivalent (CEV)
 - $\leq 0.45\%$ for grades with SMYS ≤ 360 N/mm² and
 - $\leq 0.48\%$ for grades with SMYS > 360 N/mm².
- Body shall be normalized or normalized and tempered.



Hellenic Gas Transmission System Operator S.A.
357-359 Messogion Av., GR 152 31 Halandri
Tel.: 213 088 4000
Fax: 210 674 9504
Email: desfa@desfa.gr

TECHNICAL SPECIFICATION

Doc No: DSF-SPC-PIP-024

Rev. 2

Page 9 of 14

3.5.3 PLUG

Carbon steel (similar material to body).

3.5.4 COVER

As per ELOT EN 1503-1.

3.5.5 STEM SEALS

Suitable elastomer.

3.6 NON DESTRUCTIVE EXAMINATION

All items shall be radiographically, ultrasonically or magnetic particle examined according to EN 14141. Radiographic films during shop inspection performed by Owner's TPI shall be available at request.

3.7 FIRE TEST

If so specified on the data sheet valve design shall have been qualified as per EN ISO 10497.

"Fire-safe" certification shall include "fire-safe" tests representing all sizes and pressure ratings for each valve model. "Fire-safe" tests shall be witnessed by the Inspector. Previous acceptance of certification by the Owner. 's Engineer is acceptable in lieu of requalification for identical valves.

3.8 FACTORY TEST

3.8.1 STRENGTH AND TIGHTNESS TEST

Air seat tests plus hydrostatic shell tests as per EN 14141 are required.

3.8.2 OPERATIONAL TORQUE TEST

Required after mounting of operating equipment and inclusive of operator functions.

3.9 SURFACE TREATMENT

As per Data Sheet. Valves to be installed below ground shall be coated externally by Manufacturer. External coating for buried valves shall be in accordance with Technical Specification DSF-SPC-MEC-009. Valves to be installed above ground shall be primed and painted



Hellenic Gas Transmission System Operator S.A.
357-359 Messogion Av., GR 152 31 Halandri
Tel.: 213 088 4000
Fax: 210 674 9504
Email: desfa@desfa.gr

TECHNICAL SPECIFICATION

Doc No: DSF-SPC-PIP-024

Rev. 2

Page 10 of 14

3.10 MARKING

Valves to be installed below ground shall be marked on a welding end with valve serial number, Client contract number and material grade of welding end, and all marking shall be as per EN 13942 on the nameplate which shall be fixed at a point close to the actuator / operator.

Valves to be installed above ground shall be marked on their bodies with serial number and Client contract number. Welding ends shall be marked with material grade, and all marking shall be as per EN 13942 on the nameplate.

The nameplate shall additionally bear the Inspection Body stamp as per EN 10204 and Technical Specification DSF-SPC-QAC-005.

3.11 TAGGING

All valves shall be tagged with the valve number (commodity code) as stated on the data sheet and be prefixed by the valve nominal size. This shall be clearly stamped on a non-corrodible metal tag which is to be securely attached to the valve with a non-corrodible metal wire.

3.12 DELIVERY

When wrench is specified on the DATA SHEET, one piece shall be supplied with each valve.

Handle extension is required if valve is to be installed below ground.

Handwheels and wrenches may be shipped in accordance with the Manufacturer's standard procedure, otherwise the valve shall be delivered in fully assembled condition with all openings, pipe ends, nipples, etc. capped for protection. Open/ Close direction on handwheels must be clearly marked.

4 ADDITIONAL REQUIREMENTS FOR HYDROGEN USE

4.1 General Remarks

Valves shall be PED certified and comply also with EN 13942 and EN 14141.

Valves shall be designed and tested to minimize the leakage thru the stem packing.

Pressure relief system shall be carefully designed to avoid any leakage to the ambient.

To minimize the risk of leakage, threaded connections for drain and vent on valve body should be avoided.

It will be necessary to specify some additional requirements on chemistry and on hardness of CS steel components, similar to those specified for the piping forged components in ASME B.31.12. The same requirements shall apply to the pup pieces used.



Hellenic Gas Transmission System Operator S.A.
357-359 Messogion Av., GR 152 31 Halandri
Tel.: 213 088 4000
Fax: 210 674 9504
Email: desfa@desfa.gr

TECHNICAL SPECIFICATION

Doc No: DSF-SPC-PIP-024

Rev. 2

Page 11 of 14

4.2 Materials

The plug shall be manufactured from austenitic stainless-steel material X5CrNiM017-12-2 (SS 1.4401) or X2CrNiMnMoNb21.16.5.3 (SS 1.3964).

SEAT/RINGS: For Seals Viton material shall be AED (Anti-Explosive Decompression) type and suitable for 100% of H₂ (confirmed by Manufacturer). In alternative, PTFE Lip Seal material shall be used.

Spring material on X-750 can be considered provided the maximum hardness limited at 50 HRC.

Not all high strength materials such as martensitic stainless steels or high strength chrome nickel alloys normally adopted for the stem shaft are compatible with Hydrogen. Manufacturer shall confirm the suitability of the material used.

4.3 Testing

Stem seals shall be fugitive emission tested in accordance with ISO 15848-2. Test shall be carried out at both ambient and maximum design temperature with helium as fluid. The fugitive emission tightness class shall be BH ($\leq 1.78 \cdot 10^{-7}$ mbar·l·s⁻¹ per mm stem diameter).

Valves purchased to API 6D requirements shall be capable of passing the pressure tests described in API 6D Annex H, para. H4, using helium as the test medium. Other valves shall be capable of passing the pressure tests described in API 598, using helium as the test medium.

5 SUPPLEMENTARY REQUIREMENTS

The following Supplementary Requirements are also applicable.

SUPPLEMENTARY REQUIREMENT SR1

Valve seats shall provide for double block and bleed which shall function under the lowest pressure differential.

SUPPLEMENTARY REQUIREMENT SR2

Seat design shall incorporate a sealant injection system that shall allow for injection with valve under full line pressure. The system shall provide a tight shut-off even if seat sealing surfaces should become damaged.

With earth-covered valves (refer to Data Sheet) injection lines shall be extended to near valve operator. A check valve shall be where the injection line is fixed to the body.

Screwed joints are only acceptable if fully engaged and seal welded.



Hellenic Gas Transmission System Operator S.A.
357-359 Messogion Av., GR 152 31 Halandri
Tel.: 213 088 4000
Fax: 210 674 9504
Email: desfa@desfa.gr

TECHNICAL SPECIFICATION

Doc No: DSF-SPC-PIP-024

Rev. 2

Page 12 of 14

6 TECHNICAL DOCUMENTATION

6.1 QUANTITY

Three (3) copies of each inclusive of original for all Documents (including IRNs when required) and Certificates, except otherwise specified.

Three (3) of each inclusive of one reproducible for all drawings, except otherwise specified.

Also electronic files (word documents and/or AutoCAD documents as applicable and scanned PDF files) of all Documents and Certificates must be submitted by Vendor to the Owner.

All documents of final documentation package shall be checked and originally signed by Owner's TPI when required.

6.2 INSPECTION AND CERTIFICATION

Inspection will be performed by an Independent Accredited Inspection Body or/and the Manufacturer's Authorized representative independent of the manufacturing department.

Inspection requirements are defined in the following documents:

- a. Material requisition
- b. Technical Specification DSF-SPC-QAC-005 "Shop inspection of equipment for NGT and material project"
- c. Relevant project specifications
- d. Inspection clauses of applicable Standards.

Inspection procedures to be followed are detailed in DESFA document "Inspection and Test instructions".

6.3 DOCUMENT REQUIREMENTS

WITH TENDER

Proof of design either as certificate of approval or prototype test report issued by an Accredited certifying authority.

Statement of Manufacturer's type number for each item if standard product offered. Catalogues, general arrangement drawings and parts list covering all items inclusive of operating equipment.

Statement regarding materials used for all principle component with reference to material standards herein.

Statement regarding materials for surface treatment.



Hellenic Gas Transmission System Operator S.A.
357-359 Messogion Av., GR 152 31 Halandri
Tel.: 213 088 4000
Fax: 210 674 9504
Email: desfa@desfa.gr

TECHNICAL SPECIFICATION

Doc No: DSF-SPC-PIP-024

Rev. 2

Page 13 of 14

Certificate confirming valve design has been qualified for Fire Test Approval, if required.

AFTER AWARD OF CONTRACT (BEFORE PRODUCTION)

Dimensioned general Arrangement drawing of each item including support ribs, operating equipment etc., together with a material parts list detailing material standard and grade, item number and description as well as certification level of materials as a minimum.

Welding procedures specifications, Forming procedures, Testing procedures.

Recommended procedure for installation (welding) in pipeline to avoid excessive heat on valve.

Manufacturer's Detailed Test and Inspection plan. The plan shall additionally show the control points at which the Independent Inspectors witnessing /approval is required as per section 5.2 herein.

ON DELIVERY

Comprehensive operation, maintenance and reconditioning manuals.

List of recommended tools, spare parts, lubricants etc., necessary for two years operation.

6.4 VALVE CERTIFICATION PACKAGE

Valve drawings shall include the following information printed clearly in or adjacent to the title block:

- a. Contract No.
- b. Requisition No. and item No.
- c. Purchase Order No.
- d. Valve number (Commodity Code)
- e. The principle dimensions of the valve, any gear operator, the size, type, and style. Also the weight of the valve, per size, should be included.
- f. Materials of construction.
- g. Pressure-Temperature limitations.

Drawings shall be checked and certified by the Manufacturer as being an actual record of the valve being supplied against the Purchase Order.

Drawings shall be sent to Owner accompanied by a transmittal note or letter, marked for attention Procurement Department.



Hellenic Gas Transmission System Operator S.A.
357-359 Messogion Av., GR 152 31 Halandri
Tel.: 213 088 4000
Fax: 210 674 9504
Email: desfa@desfa.gr

TECHNICAL SPECIFICATION

Doc No: DSF-SPC-PIP-024

Rev. 2

Page 14 of 14

Approval of Manufacturer's drawings shall not be considered as relieving the Manufacturer of any responsibility for detailed design, dimensions and construction of equipment or deviation from specification.

Manufacturer shall not commence final manufacture of valves until receipt Owner's approval of his drawings.

7 SHIPMENT

- Valves shall be shipped in the open position.
- Unmachined exterior surfaces of valves shall be painted as per Manufacturer's standard.
- Machined or threaded surfaces subject to atmospheric corrosion during shipment or subsequent storage shall be coated with easily removable rust preventive.
- Valves with screwed or socket weld parts shall have the ends protected with metal, or plastic plugs.
- Valves with flanged ends shall have the gasket surface protected by means of a suitable disc wired on.
- Valves with butt-weld ends shall have the bevels covered with a suitable close fitting protector.
- When lifting the valves, the slingers must be wrapped around the body only and not around the spindle lever.
- Packing is to be in wood cases.
- The valves to be transported must be firmly fixed to the case load-bearing bottom.
- For valves with a weight greater than 0.6 tons fastening is performed with wooden saddles and joists nailed to the side walls. The saddles two for each valve, must ensure an uniform distribution of the valve weight over the case bottom. For valves with a weight lighter than 0.6 tons only the joists nailed to the side walls are required. For the valve actuator units and the valve components (e.g. extensions) the fastening will depend upon their shape, weight and dimensions.
- The packing shall be mechanically protected i.e. from impact caused by falls during handling, vibration caused by transport etc.
- Manufacturer's Quality Plan shall include details about lifting, support during transportation, preservation, etc.